Adatlap | Cikkszám: 249-130

Fecskendő; Tartalom: 20 ml Alu-Plus kontakt paszta



Műszaki információk

Elsődleges termékfunkció	"Alu-Plus" kontakt paszta

Anyag információk

Tűzterhelés	0 MJ
Tömeg	35.3 g

Kereskedelmi adatok

Product Group	2 (Terminal Block Accessories)
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 8.0	EC002848
ETIM 7.0	EC002848
Csomagolási egység	20 (5) Stück
Csomagolás típusa	Box
Származási ország	DE
EAN/VTSZ	4017332133890
Vámtartifaszám	34039900900

Letöltések

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 249-130

Documentation

Bid Text

249-130	17.05.2017	doc 23.50 KB
249-130	19.02.2019	xml 2.49 KB


CAD/CAE-Data

CAE data

EPLAN Data Portal
249-130

Szerelési útmutató

Alkalmazás




WAGO Rail-Mount Terminal Blocks (up to 4 mm²/12 AWG)
For each conductor entry: Insert nozzle of the “Alu-Plus” syringe in every open conductor entry hole (one after the other).




Press plunger down until “Alu-Plus” has filled all conductor entry holes.

Alkalmazás




WAGO Lighting Connectors
Push nozzle of the “Alu-Plus” syringe first into the circular entry and then into the square conductor entry hole of the WAGO Lighting Connector.




Press the plunger down until “Alu-Plus” has filled both entry holes.

Note: Not suitable for higher temperature applications!

Alkalmazás



1. Push nozzle of the “Alu-Plus” syringe into every open conductor entry hole (one after the other).



2. Press plunger down until “Alu-Plus” has filled all conductor entry holes.